ROOM FINISH SCHEDULE – B2903

Note: All materials shall be submitted for review and approval by the DPW COR prior to installation/fabrication.

Wall Paint Color: Match existing color. Eggshell Finish.

Acoustical Ceiling Tile: Armstrong 'Kitchen Zone' 672

Ceiling Grid: Prelude 15/16-inch Suspension System (as needed).

Cabinet Specifications:

- Oak wood with Minwax 'Heirloom Oak' MW 441.
- All plywood CARB compliant box construction, solid 1/2-inch-thick engineered wood for back and sides.
- Solid Oak door frame with 1/2-inch-thick Oak center panel.
- Shaker doors with 3-inch-wide frames and flat recessed center panels.
- 3/4-inch-thick Oak adjustable shelves with clear heavy duty locking shelf supports.
- 2 full depth adjustable shelves (Wall Cabinets)
- 1-1/2 depth adjustable shelves (Base Cabinets)
- All wall cabinets shall be 12 inches deep.
- All base cabinets shall be 24 inches deep.
- All base cabinets shall have a drawer with full access hidden glides system
- Provide 2 – 4 drawer base cabinets.
- Concealed heavy duty 6-way adjustable steel door hinges.
- 2 door bumpers per door/drawer.
- Toe kick to match cabinet finish.
- Provide 3-inch satin nickel bar pulls at all wall cabinets, base cabinets and drawers.

Countertop: 1-inch quartz agglomerate solid surface countertop and 4-inch backsplash, homogeneous filled solid polymer. Straight or quarter round edge profile.

Backsplash Tile: 4-1/4-inch x 12-3/4-inch Daltile Modern Dimensions, semi-gloss. Color: 0190 Artic White with running bond installation.

Grout: Laticrete Spectralock Pro Premium Grout 'Bright White'

Sealant: Clear silicone sealant. Provide continuous bead of caulk where countertop and tile meet.

Kitchen sink: Top mounted, single compartment, 20 gage stainless steel with integral mounting rim for flush installation, minimum dimensions of 30-inches wide by 21-inches, with undersides fully sound deadened, with supply openings for use with top mounted washerless sink faucet with hose spray and 3.5 -inch drain outlet. Provide stainless steel drain outlets and stainless-steel cup strainers. Provide separate 1.5 -inch p-trap and drain piping to vertical vent piping from each compartment.

Kitchen Faucet: Provide top mounted washerless sink faucet with hose spray. Water flow rate must not exceed 8.3 L per minute 2.2 GPM when measured at a flowing water pressure of 414 KPA 60 psi. Provide aerator with faucet. Faucet color brushed nickel.

Drinking Fountain: Elkay ezH20 Bottle Filling Station and Single ADA Cooler Non-Filtered Refrigerated Light Gray Model # EZS8WSLK or approved equal.

Mini-Blinds: 2-inch slats, vinyl, cordless, color white, mounted inside frame. Provide mounting hardware and all operating components.