SALIENT CHARACTERISTICS

<u>CRANE MIN SPECIFICATIONS</u>

- CAPACITY MAX: 6,680 LBS @ 8 FT. 5,000 LBS @10 FT.
- BOOM LENGTH 39.8 FT
- RETRACTED 11.6 FT
- HOOK HEIGHT 41.3 FT
- 4 OUTRIGGERS MULTI POSITION
- SWING DESIGN 360 DEG. NON-STOP
- OUTRIGGER WARNING POSITIONING INTERLOCK WITH DISPLAY
- ONBOARD SELF DIAGNOSTIC COMPUTER SYSTEM
- RADIO REMOTE CONTROL INFINATLY VARIABLE
- FOUR PART LOAD BLOCK AUTOMATIC HOOK STOW
- WARRANTY 12 MONTHS MINIMUM
- COLOR TAN
- HYDRAULIC PUMP VARIABLE DELIVERY PISTON
- CRAWLING GEAR ENDLESS RUBBER CRAWL
- HILL CLIMBING 23 DEGREES
- ENGINE: JP-8 COMPATIBLE
- STEERING HYDRAULIC INDEPENDENT
- SAFETY (LMI) LOAD MOMENT INDICATION (P.A.T. SYSTEM)
- SAFETY AUTOMATIC WINCH BRAKE
- SAFETY WIRE ROPE LIMITER
- SAFETY EMERGENCY STOP BUTTON
- CONTROL VALVE ELECTRONIC
- SINGLE PERSON WORK PLATFORM, BOOM TIP MOUNTED

OTHER REQUIREMENTS

Recommended Spare Parts Maintenance Package (2 Years)

MILAR Non-Marking Tracks, pair Note: Ships with standard tracks

Hyd. Tilt Deck Trailer: Equipped with track mats, fuel jugs, outrigger pads, rigging box, spare tire and a custom ramp with tie downs