Salient Characteristics for Fiber Optic Splice

Trailer 09 April 2026

- 6.0KW NPS Gas Generator
- 20 gallon fuel tank
- 50 amp load center
- 25’ shoring cord
- 60 amp converter/charger
- 12V battery cutoff switch
- Full aluminum frame
- Torsion axels
- All aluminum tubing construction
- Electric breaking
- ST20575R15 Tires on steel wheels w/ spare included
- 7-way trailer plug
- Adjustable height coupler w/ 2 5/16” pintle eye
- 5000 lb jack
- Safety chains & hooks
- LED Clearance Lights
- Exterior Gas fuel fill
- Exterior 120V GFI protected outlet (15 amp)
- Roof mounted strobe light
- LED tail lighs
- (2) 24” entrance doors w/ windows
- Aluminum slide out step at side door
- Front & Rear stabilizer jacks
- Lighted direction arrow board
- (2) surface mounted LED flood lights
- (2) cable access doors w/ brushes
- (2) .3”x20” tinted horizontal slide windows
- 5200 BTU Electric wall heater
- Hardwired carbon monoxide detector
- (6) Surface mounted LED Ceiling lights
- Eye was station
- Dual 12V USB Outlet
- Insulated walls & ceiling
- 1A-10BC Fire Extinguisher
- (5) 120 V Interior Outlets – 15 amp

- 12V power roof vent
- 12V AM/FM Bluetooth stereo w/ (4) interior speakers
- 13500 BTU Roof mounted air conditioner
- (2) Cable Clamps
- 4” laminate overhead cabinet
- Road-side laminate cabinets

Photo Example:

Manufacturer and Model Examples:

InTech FOST8x12TA2

Altec 8x12