PLUMBING FIXTURES

TAG	FIXTURE		TRIM						DESCRIPTION	CONNECTION						
	TYPE	MANUFACTURER AND MODEL NUMBER	TYPE	MANUFACTURER AND MODEL NUMBER	TYPE	MANUFACTURER AND MODEL NUMBER	TYPE	MANUFACTURER AND MODEL NUMBER		WASTE	VENT	TRAP	COLD WATER		HOT WATER	
													BRANCH SUPPLY	STOP INLET	BRANCH SUPPLY	STOP INLET
WC-1	WATER CLOSET FLOOR MOUNTED BARRIER-FREE	AMERICAN STANDARD 3641.001 OR EQUAL	FLUSH VALVE	SLOAN ROYAL 111-1.28 OR EQUAL					WHITE VITREOUS CHINA, FLOOR MOUNTED SIPHON JET, ELONGATE BOWL, 1.28 GALLONS PER FLUSH, 1-1/2" TOP SPUD INLET, BARRIER-FREE HEIGHT 1.28 GALLONS PER FLUSH, EXPOSED MANUAL DIAPHRAGM FLUSHOMETER, SIDE OSCILLATING HANDLE, 1-1/2" TOP SPUD CONNECTION	4"	2"	INTEGRAL	1-1/2"	1"	-	-
L-1	LAVATORY WALL HUNG BARRIER-FREE	AMERICAN STANDARD DECORUM OR EQUAL	FAUCET	CHICAGO FAUCET 2200-4 OR EQUAL	MIXING VALVE	SYMMONS 7-225-CK	IN-LINE CHECK VALVE	CIRCLE SEAL 2200 SERIES	20" X 18" WHITE VITREOUS CHINA, WALL HUNG, SINGLE FAUCET HOLE, DRILLED FOR CARRIER SUPPORT, MOUNT 34" AFF TO RIM TO BE BARRIER-FREE SINGLE HANDLE, E12 AERATOR EXPOSED LEAD-FREE MIXING VALVE, CHECK/STRAINERS ON INLETS, TAMPER RESISTANT CAP, 0.5 GPM MINIMUM FLOW	1-1/2"	1-1/2"	1-1/4"	1/2"	1/2"	1/2"	1/2"
JS-1	JANITOR'S SINK	FIAT TSB-200 OR EQUAL	FACUET	CHICAGO FAUCET 782-E27 OR EQUAL	HOSE AND BRACKET	FIAT 832-AA			STAIN RESISTANT, WHITE, PRE-CAST TERRAZZO, 24" X 24" X 12", INTEGRAL STAINLESS STEEL GRID STRAINER DRAIN OUTLET, 3"P-TRAP TO MATCH PIPING SYSTEM. TYPE 304 STAINLESS STEEL WALL GAURDS, 20 GA, 12" HEIGHT, LOCATED ON TWO WALLS. CAST OR WROUGHT COPPER ALLOY, COMBINATION FAUCET MOUNTED 36" ABOVE FINISHED FLOOR. SPOUT SHALL HAVE PAIL HOOK, 3/4" HOSE CONNECTION, WALL BRACE, CONCEALED INTEGRAL STOPS, 8" CENTERS. CAST, COPPER ALLOY HANDLES. COPPER ALLOY OR CRS ESCUTCHEON. IN-LINE ASSE 1001 VACUUM BREAKER. EXPOSED PARTS SHALL BE CHROME PLATED. 30" LONG, 5/8" RUBBER HOSE AND STAINLESS STEEL HOSE BRACKET. MOUNT BRACKET MINIMUM 18" ABOVE FINISHED FLOOR AND 6" LEFT OF FAUCET CENTER	3"	1-1/2"	3"	3/4"	1/2"	3/4"	1/2"
DELETED																
1 EWC-1	ELECTRIC WATER COOLER	ELKAY LZSTL8WSSP							WALL MOUNTED SELF-CONTAINED MODULE WITH BOTTLE FILLING, STAINLESS STEEL BOWL, DRAIN AND FLOW RESTRICTING BUBBLER. VINYL COVER SHALL BE DESIGNER COLOR AS SELECTED BY ARCHITECT. MOUNT UNIT FOR BARRIER-FREE ACCESS.	1-1/2"	1-1/2"	1-1/4"	1/2"	1/2"	-	-

ELECTRIC POINT OF USE WATER HEATERS

TAG	BASIS OF DESIGN MANUFACTURER AND MODEL OR EQUAL	WATER SIDE				ELECTRICAL					REMARKS
WH		MIN. FLOW (GPM)	MAX. FLOW (GPM)	EWT (°F)	LWT (°F)	NUMBER OF ELEMENTS	ELEMENT WATTAGE (kw)	VOLT	PH	SCCA (MIN.)	
1	EEMAX PROSERIES XTP020480	0.5	20	38	110	2	20	480	3	65	
2	EEMAX PROSERIES XTP020480	0.5	20	38	110	2	20	480	3	65	
3	EEMAX PROSERIES XTP020480	0.5	20	38	110	2	20	480	3	65	

DRAINS AND CLEANOUTS

TAG	BASIS OF DESIGN MANUFACTURER AND MODEL OR EQUAL	DESCRIPTION
FD-1	ZURN ZN415B-P-VP	6" ROUND FLOOR DRAIN W/ NICKLE BRONZE TOP, 1 TRAP GUARD, CLAMPING COLLAR
FD-2	ZURN Z668-VP	11"x19" RECTANGULAR AREA FLOOR DRAIN W/ CAST IRON VANDEL PROOF TOP, NO HUB CONNECTION
HD-1	ZURN Z1870-ZM	6" TO 4" OPEN HUB DRAIN, 316 STAINLESS STEEL, NO HUB CONNECTION 1
DELETED		
FCO	ZURN Z1400-ZN-VP	FLOOR CLEANOUT, CAST IRON, EXTRA HEAVY DUTY TOP
RD-1	ZURN Z-Z164-G	12" DIA COMBINATION MAIN & OVERFLOW DRAIN LOW SILHOUETTE DOME, 6" PIPING CONNECTION, NO-HUB CONNECTION, AND UNDERDECK CLAMP.
RD-2	ZURN Z199-DC-CP-VP	DOWNSPOUT NOZZLE W/ CHROME PLATED COVER, STAINLESS STEEL HINGED STRAINER

BACKFLOW PREVENTER (RPBP)

TAG	SERVICE	LOCATION	BASIS OF DESIGN			REMARKS
			MANUFACTURER OR EQUAL	MODEL	SIZE (IN)	
RPBP-1	MAIN	METER ROOM	WATTS	994	4"	

NO.	REVISION	DATE	BY
1	ADDENDUM 1	06/11/2026	AEI

SEAL

DESIGNED: Designer
CADD Author
TECH. REVIEW: Checker
DATE: 12/19/2025

SUB SHEET NO. P4

TITLE OF SHEET: PLUMBING SCHEDULES

HANGARS 3 & 4 REHABILITATION

DRAWING NO. 646 190066
PMIS/PKG NO. GATE 308504
SHEET 135 OF 153

Autodesk Docs://GATE Floyd Bennett Field/24200-03_GATE_Mechanical_R26.rvt
6/10/2026 10:38:08 PM