ROOM FINISH SCHEDULE

Note: All materials shall be submitted for review and approval by the DPW COR prior to installation/fabrication.

Flooring: Tarkett VCT II 533 'True Beige' WB.
Wall Base: Tarkett Traditional Wall Base 283 'Toast'.
Ceiling Paint Color: Sherwin Willams SW 6126 'Navajo White' – Eggshell Finish (At hard ceilings).
Wall Paint Color: Sherwin Willams SW 6126 'Navajo White' – Eggshell Finish.
Acoustical Ceiling Tile: Armstrong 'Kitchen Zone' 672.
Ceiling Grid: Prelude 15/16-inch Suspension System (as needed).
Hollow Metal Doors & Door Frames: Sherwin Willams SW 7513 'Sanderling' – Semi-gloss Finish.

Cabinet Specifications:

- Oak wood with Minwax 'Heirloom Oak' MW 441.
- All plywood CARB compliant box construction, solid 1/2-inch-thick engineered wood for back and sides.
- Solid Oak door frame with 1/2-inch-thick Oak center panel.
- Shaker doors with 3-inch-wide frames and flat recessed center panels.
- 3/4-inch-thick Oak adjustable shelves with clear heavy duty locking shelf supports.
- 2 full depth adjustable shelves (Wall Cabinets)
- 1-1/2 depth adjustable shelves (Base Cabinets)
- All wall cabinets shall be 12 inches deep.
- All base cabinets shall be 24 inches deep.
- All base cabinets shall have a drawer with full access hidden glides system
- Provide 2 – 4 drawer base cabinets.
- Concealed heavy duty 6-way adjustable steel door hinges.
- 2 door bumpers per door/drawer.
- Toe kick to match cabinet finish.
- Provide 3-inch satin nickel bar pulls at all wall cabinets, base cabinets and drawers.

Countertop: 3/4-inch quartz agglomerate solid surface countertop and 4-inch backsplash, homogeneous filled solid polymer. Round top and bottom edge profile.
Backsplash Tile: 4-1/4-inch x 12-3/4-inch Daltile Modern Dimensions, semi-gloss. Color: Biscuit' K175 with running bond installation.
Grout: Laticrete Spectralock Pro Premium Grout 'Bright White'
Sealant: Clear silicone sealant. Provide continuous bead of caulk where countertop and tile meet.