Salient Characteristics of the Anton-Paar SVM 3001 Viscometer

Commercial Availability Certification:
I have evaluated the commercial marketplace and determined that the salient characteristics documented below are available in products/services offered in the commercial marketplace.

Item Number	Part Description	Quantity
105001	SVM 3001SMART VISCOMETER- Dynamic viscosity: 0.2 to 30 000 mPa.s Kinematic viscosity: 0.2 to 30 000 mm²/s Density: 0 to 3 g/cm³ Temperature range: -60 to +135 °C Counter-cooling required below -20 °C	1 ea
P01079	Anton Paar Preventive Maintenance On-Site This service includes: - Check of the instrument and ambient conditions - Instrument cleaning - Replacement of normal wear parts - Inspection of critical components - Adjustments as needed - Performance Verification - Maintenance Report This service will be carried out at the customer's facility by a certified Anton Paar service engineer following relevant factory standards, using calibrated	2 ea

	and certified tools.	
65085	DRYING CARTRIDGE Drying cartridge for absorbing humidity from ambient air. Use the drying cartridge to prevent condensation if drying with the air pump. Comes with: hose 2.5x4 polyurethane transparent hose 4x6 polyurethane black (hose connector 6 mm / 4 mm)	1 ea
6442	SYRINGES 10 ml LUER (100 pcs.)	1 ea
424100	AP Connect STANDARD SOFTWARE FOR PAPERLESS LAB SOFTWARE FOR DIGITAL LABORATORY DATA FLOW AND PAPERLESS DATA HANDLING.	1 ea

Contracting Officer:

8/7/2026 X Joseph Dellinger
Contracting Officer (KO) Signed by: USA