Meet Specifications Listed

Hydraulic Test Stand, Electric, 2-System (Independent)	Comments
Condition: New	
Power:	
3 phase, softstart electric motor available in 480 VAC (60 Hz)	
Frame/Chassis:	
Finish: Durable Powder Coat	
Max Length: 76 in (193 cm)	
Max Width: 90 in (229 cm)	
Max Height: 58 in (147 cm)	
Max Weight Lb (Kg):5000 (2268)	
Forklift Slots	
Heavy Duty Casters	
Pump System:	
Fluid:MIL-PRF-5606/83282	
Adjustable working pressure, two independent systems	
Adjustable pressure compensated, variable volume, piston pump	
Two large fluid coolers with 3 phase electric fan	
Two high efficiency, non-bypassing pressure filters with 2-micron absolute, Microglass III element (Beta rating > 200 based on ISO 4572)	
Two large capacity return filters with 5 micron absolute, Microglass III element (Beta rating > 300 based on ISO 4572)	
Pump Flow System 1 Gpm (Lpm):34 (129)	
Pump Flow System 2 Gal (L):20 (76)	
Pressure Gauge Psi (Bar):6,000 (410)	
Pressure Range Psi (Bar):250-4,000 (17.2-276)	
90 gal (341 l) stainless steel reservoir with desiccant air filtration canister	
Electric reservoir fill system with 2-micron filter and coupling	
Instumentation:	
Two 2-48 gpm (8-180 lpm) dual scale flow meters	
Two dual scale pressure gauges	
High Fluid temperature (>160º F) shut off switch with LED indicator light, each system	
Electric over temperature switch	
-40 to 180º F (-40 to 80º C) dual scale pyrometer, each system	
Hourmeter	
Electric high-low reservoir level	
Misc.	
Electric clogged filter indicator	
Easy access fluid sampling valves (meets ANSI T2.24.1-1991)	
LED backlit return sightgauges	
Quick disconnect hydraulic couplings	
Standard 25 ft (7.62 m) pressure and return hoses, two sets	
Standard 50 ft. (15.24 m) input power cord without input plug	
Hose trays and hangers	
Stainless steel drip pan	
Pressure Hose System 1 Size:16 (1)	
Pressure Hose System 2 Size:12 (.75)	
Return Hose System 1 Size:24 (1.5)	
Return Hose System 2 Size:16 (1)	

Runaround Kit (option)	desired not required
Manuals: Operations, Parts, Maintenance	
Delivery:	
FOB to Edwards, CA	
ETA ARO 180 Days	