Specifications
Distant Discharge Plow
Brand Name Only
Grand Teton National Park

PROJECT DESCRIPTION / SUMMARY:

This project shall procure and deliver to Grand Teton National Park a specific Plow unit for plowing Roads and Highways in Grand Teton National Park. Plow specifications shall match as specified herein (Brand Name Only) in order to operate with existing equipment and parts.

SPECIFICATIONS:

Bonnell Industries 12DD42MX1

- **Model Distant Discharge Two eared steel plow**
- Painted Orange Polyurethane Enamel
- 12’ Cutting Edge x 42” Straight Height x 58” Discharge Ear Height Moldboard Trip
- (2) Heavy Duty extension Spring assemblies with 6 total springs
- Heavy Duty tubular table A-Frame assembly

- (2) 4 x 12 Reversing Cylinders
- (5) Table to moldboard hook-up points
- Level Raise Lift System with lift chains for high country plow
- Swivel Bar with push ears 30-1/2” on center (plow section installed)
- ¾” bottom angle moldboard weldment angle
- 3/8” x 12” rubber flap kit installed
- Extended front push beam on table approx..144” long
- Plow stand installed
- Must fit a 60,000 GVW dual rear axle dump truck affixed with a wing plow.

DELIVER TO:

Grand Teton National Park
Moose Warehouse
C/O Clinton Vaughan
103 Headquarters Loop
Moose WY, 83012,