ABRASIVE GRIT BAG SPECIFICATIONS LSN 5350-HM-CN1-4678:

- FOR USE WITH: GRIT, SANDBLAST, UTILITY GRADE, #16-30 SIEVE SIZE, MIL-PRF-22262(LATEST), 2000 LBS/ONE TON, 5:1 SAFETY FACTOR
- TUBULAR DESIGN
- 190 GSM OR 5.5 OZ PER SQ YARD MINIMUM THICKNESS, UNCOATED FABRIC, UV TREATED
- 4/10" ABOVE BAG WHITE PICK-UP POINT LOOPS
- 14 X 18 INLET SPOUT WITH WEB TIE (PLAIN DUFFLE TOP ACCEPTABLE).
- 1.5" WHITE PICK-UP POINT PERIMETER BAND
- 10 X 20 OUTLET SPOUT W/ STAR CLOSURE
- STAR CLOSURE HAS PROTECTIVE FLAP CORD ROPE
- 3.0 MIL MINIMUM THICKNESS LDPE INNER LINER ATTACHED WITH 8 TABS
- LARGE ROPE LOCK ON OUTER CLOSURE
- (2) 12 X 12 ZIP LOCK POUCHES SEWN IN TOP SEAM, (SAME SIDE AS PRINTED COMPANY LOGO, IF LOGO IS PRINTED ON BAG). DO NOT COVER PRINTED INFO
- ADDITIONAL MARKING REQUIREMENTS, EACH SACK SHALL BE MARKED WITH THE FOLLOWING INFO:
  1) STOCK NUMBER: 5350-HM-CN1-4678
  2) BATCH OR LOT NUMBER (DOCUMENTATION/COCs SENT FOR ALL BATCHES/LOTS SUPPLIED MUST MATCH BAG MARKINGS)

  NOTE: VENDOR TO INSERT FIBERBOARD OR PLYWOOD BETWEEN EACH BAG & PALLET TO PREVENT SAGGING AND PUNCTURE FROM LIFTING FORKS. EXERCISE CAUTION IF STACKING FOR SHIPMENT, USING PROPER DUNNAGE AND SHORING.

6/16/2022 revised by adding 6.5 oz/sy outer bag fabric weight.
Changed 4.0mil inner liner to 3.0 mil.

7/5/2022 revised outer bag fabric weight from 220gsm & 6.5 oz/sy to 190gsm & 5.5oz/sy.
Added “plain duffle top acceptable” in lieu of top inlet.