Compact Track Loader -Caterpillar CAT 265 or Equal, 12- Month Rental
Include Pricing: Weekly/Monthly

1. Engine & Performance
    Power: 72–79 HP, turbocharged diesel.
    Emissions: EPA Tier 4 Final & EU Stage V compliant.
    Cold Weather: 120V engine block heater included.
2. Weight, Capacity & Dimensions
    Operating Weight: 9,500–11,000 lbs.
    Operating Capacity (ROC): 2,820–3,100 lbs (at 35% tipping load).
    Max Dimensions: 88" Height, 85" Width (designed for confined access).
    Maneuverability: Zero-radius turning capability.
3. Hydraulics & Load Management
    Power: 3,500–3,800 PSI and 23–32 GPM flow rate.
    Connections: Hydraulic quick coupler and auxiliary connectors.
    Features: Visible oil sight gauge and "Ride Control" load cushioning.
4. Undercarriage
    Tracks: Steel-imbedded rubber tracks for multi-terrain traction.
5. Cab & Operator Ergonomics
    Enclosure: Fully enclosed, pressurized cab with HVAC.
    Controls: Joystick controls (pilot-operated or selectable).
    Seat: Adjustable Air Ride suspension seat.
6. Safety & Lighting
    Standards: ANSI/SAE compliant; ROPS/FOPS approved cab.
    Visibility: LED front/rear work lights, auto-reverse lights, and backup camera.
    Safety Interlocks: Seatbelt required; raising armrest/leaving seat disables hydraulics and engages parking brake.
    Alerts: Automatic backup alarm.
7. Required Attachments
    Bucket: 75"–85" dirt bucket with replaceable cutting edge.
    Forks: 48" heavy-duty pallet forks with carriage.

Electric Forklift - Drexell SL120AC Electric Swing Mast Forklift (VNA) or Equal, 12- Month Rental
Include Pricing: Weekly/Monthly

1. Performance & Environment
    Power: Electric, 72V system.
    Capacity: Minimum 12,000 lbs at 24" load center.
    Maneuverability: 72" (6 ft) VNA clearance; dual front- and side-loader capability.
    Steering & Drive: Power steering; multi-directional, articulating, or pivoting steering.
    Speed: Minimum 5 mph loaded.
    Dimensions: Max 70" width, Max 110" turning radius.
    Durability: Indoor/Outdoor rated with sealed, weather-resistant AC motors (IP54 rating).
2. Mast & Hydraulics
    Mast: Duplex/2-Stage, min 108" max fork height, min 48" free lift.
    Tilt: Minimum 3° forward / 5° rear.
    Forks & Hydraulics: Min 40" taper tip forks; min 4-function hydraulics.
    Load Manipulation: Integrated side-shifter, fork positioner, and side-reach.
3. Electrical System
    Control System: AC controls.
    Power Source: Compatible industrial 72V battery and charger included.
    Monitoring: Battery discharge indicator and hour meter.

4. Safety, Standards & Ergonomics

Compliance: ANSI/ITSDF B56.1 and UL "EE" (UL 583 spark-proof) certified.
Tires: Non-marking polyurethane or solid-pneumatic hybrid (indoor/outdoor).
Operator Guard: 4-post overhead guard.
Visibility: Headlights, rear work lights, strobe light, and horizontal fork indicator.
Alerts & Safety: Seatbelt, operator presence safety switch, backup alarm, and horn.
Controls: Adjustable steering column, power brakes, and manual parking brake.